



NOTE: UNLESS OTHERWISE SPECIFIED.

1. CONSTRUCTION:

NYLON HOUSING AND KNOB. STAINLESS STEEL SCREW AND NUT. ALUMINUM INSERT. COPPER RING TERMINAL. HEAT TREATED STEEL PINS

2. FEATURES:

1. THUMB SCREW CLAMPING FOR POSITIVE CONNECTION.
2. FULLY INSULATED.
3. AVAILABLE IN BLACK, RED AND YELLOW
4. 35 NEEDLES TO MAKE CONNECTION WITH THE SMALLEST OF WIRE.
5. "V" GROOVE TO CENTER WIRE TO BE TESTED.
6. MAX WIRE DIAMETER UP TO .150" (3.8MM) CAN BE CONNECTED.
7. UNITS WITH COAX CABLE ALSO AVAILABLE.
8. MOLDED NYLON HOUSING, RESISTS MOST CHEMICALS.

<h2 style="margin: 0;">E-Z-HOOK</h2>		DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A.
SCALE: DO NOT SCALE DRAWING	DRAWN BY: S.B.W.	
DATE: 9/25/07	APPROVED BY: S.B.W.	
IDNT. NO: 08505	REVISION: ----	
DESCRIPTION:		
INSULATION PIERCING WIRE CLAMP		
MODEL NO: XB		